

# 5200

Series

The grade 1 adjustable solution  
for cylindrical locksets

**hes**  
ASSA ABLOY

## Specifications

- UL 1034, burglary-resistant listed •
- ANSI/BHMA A156.31, Grade 1 •
- Patent #5,934,720 •

## Standard Features

- Tamper resistant •
- Static strength 1,500 lbs. •
- Dynamic strength 70 ft-lbs. •
- Endurance 500,000 cycles •
- Field selectable fail secure/fail safe •
- Dual voltage 12 or 24 VDC/VAC •
- In-frame horizontal adjustment •
- Non-handed •
- Internally mounted solenoid •
- Accommodates 5/8" - 3/4" latchbolt (3/4" with 1/8" door gap) •
- Strike body depth 1-3/16" •
- Plug-in connector •
- Trim enhancer included •
- Five year limited warranty •

## Optional Features

- LBM - Latchbolt monitor •
- LBSM - Latchbolt strike monitor •

## Electrical

- .24 Amps @ 12VDC/VAC •
- .12 Amps @ 24VDC/VAC •
- DC continuous duty/AC intermittent duty only •

## Finishes

- 630 - Satin stainless steel •
- 605 - Bright brass •
- 606 - Satin brass •
- 612 - Satin bronze •
- 613 - Bronze toned •
- 629 - Bright stainless steel •
- BLK - Black finish •

## Frame Application

- Metal •
- Wood •

