

# **SP-2570N**

Flush Mount Ceiling Speaker



## **DESCRIPTION:**

The SP-2570N is a ceiling speaker used for paging and background music. It is equipped with a 25/70V transformer with five wattage taps up to 5W. The speaker is mounted to a round steel baffle, finished with a white powder-coated epoxy. An optional ceiling support bridge (SSB-2) is available for installations in drop tile ceilings. Designed for indoor use only.

#### **FEATURES:**

- Flush mount in ceiling
- 8" dual cone speaker, 8Ω
- Works with 25V or 70V amplifier outputs
- Five wattage taps from 1/3W to 5W
- Round white steel baffle
- Excellent sound and reproduction for music and paging

#### **Transformer Wattage Taps:**

Transformer Wattage Taps.			
70.7V LINE		25V LINE	
Com:	Black	Com:	Black
5W:	Green	5W:	Brown
2.5W:	White	2.5W:	Red
1.25W:	Blue	1.25W:	Orange
0.625W:	Gray	0.625W:	Green
0.312W:	Violet	0.325W:	White
Secondary (Speaker direct): 8Ω			

## **SPEAKER SPECIFICATIONS:**

Size: 8"

Magnet Weight: 5 oz.

Magnet Material: Ceramic

Impedance:  $8\Omega$ DC Resistance:  $7.4\Omega$ Voice Coil Dia.: 3/4"

Power Handling: 8W RMS

Freq. Response: 65 Hz - 17 kHz

Depth: 2-¾"
Cone: Dual

Weight: 2.65 lbs. including baffle

## **BAFFLE SPECIFICATIONS:**

Type: One-step contour

Baffle Diameter: 12-1/8"

Material: 22 gauge steel

zincrometal

Finish: White semi-gloss

powdered epoxy

Depth Projection: 3/8" from surface